# SAFETY DATA SHEET

## GHEMSERVIGE .....

## 1. Identification


Product identifier	3,3',4,5-Tetrachlorobiphen	yl Solution	
Other means of identification			
Item	BZ-78K1		
Recommended use	For Laboratory Use Only		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Company name	Chem Service, Inc.		
Address	660 Tower Lane		
	West Chester, PA 19380		
	United States		
Telephone	Toll Free	800-452-9994	
·	Direct	610-692-3026	
Website	www.chemservice.com		
E-mail	info@chemservice.com		
Emergency phone number	Chemtrec US	800-424-9300	
	Chemtrec outside US	+1 703-527-3887	,
2. Hazard(s) identification			
Physical hazards	Flammable liquids		Category 2
Health hazards	Acute toxicity, dermal		Category 4
	Skin corrosion/irritation		Category 2
	Specific target organ toxicity	, single exposure	Category 3 narcotic effects
	Aspiration hazard		Category 1
Environmental hazards	Hazardous to the aquatic er hazard	ivironment, acute	Category 1

Hazardous to the aquatic environment,

long-term hazard Not classified.

OSHA defined hazards

Label elements



Category 1

Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

## 3. Composition/information on ingredients

## Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isooctane	2,2,4-Trimethylpentane	540-84-1	99.99
3,3',4,5-Tetrachlorobiphenyl		70362-49-1	0.01

#### 4. First-aid measures

4. I list-alu illeasules	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapor.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
	2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
Isooctane (CAS 540-84-1)	PEL	2350 mg/m3 500 ppm	

Components	Туре	Value	
3,3',4,5-Tetrachlorobiphenyl (CAS 70362-49-1)	TWA	0.001 mg/m3	
Isooctane (CAS 540-84-1)	Ceiling	1800 mg/m3	
		385 ppm	
	TWA	350 mg/m3	
		75 ppm	
ological limit values	No biological exposure limits noted for the ingredient(s).		
propriate engineering ntrols	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.		
lividual protection measures,	such as personal protective equipm	ient	
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear appropriate chemical resistant	gloves.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have no been established), an approved respirator must be worn. Chemical respirator with organic vap cartridge.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
neral hygiene nsiderations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

## 9. Physical and chemical properties

, ,	•
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-161.41 °F (-107.45 °C) estimated
Initial boiling point and boiling range	210.63 °F (99.24 °C) estimated
Flash point	40.1 °F (4.5 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	65.73 hPa estimated
Vapor density	Not available.
Relative density	Not available.

Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	784 °F (417.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.69867 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.7 estimated
10. Stability and reactivity	/
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition	No hazardous decomposition products are known.

## 11. Toxicological information

products

#### Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

#### Information on toxicological effects


Acute toxicity	In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. May be fatal if swallowed and enters airways. Harmful in contact with skin.		
Components	Species	Test Results	
Isooctane (CAS 540-84-1)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg, 24 Hours	
* Estimates for product may b	e based on additional compone	nt data not shown.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		

Carcinogenicity	Not classifiable as to carcinoge	nicity to humans.		
IARC Monographs. Overall Evaluation of Carcinogenicity				
	nyl (CAS 70362-49-1) d Substances (29 CFR 1910.100	1 Carcinogenic to humans.		
Not regulated.	a Substances (29 CFR 1910.100	1-1050)		
5	ogram (NTP) Report on Carcino	aens		
3,3',4,5-Tetrachlorobiphe	• • • •	Reasonably Anticipated to be a Human Carcinogen.		
Reproductive toxicity	<b>,</b>	cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause drowsiness and dizz	ziness.		
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	May be fatal if swallowed and enters airways.			
Chronic effects	Prolonged inhalation may be harmful.			
12. Ecological information				
Ecotoxicity	Very toxic to aquatic life with long lasting effects.			
Persistence and degradability				
Bioaccumulative potential				
Partition coefficient n-octanol / water (log Kow) Isooctane 5.18				
Mobility in soil	No data available.			
Other adverse effects		al effects (e.g. ozone depletion, photochemical ozone creation global warming potential) are expected from this component.		
13. Disposal considerations				

#### Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions** this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations. Local disposal regulations The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code disposal company. Waste from residues / unused Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: products Disposal instructions). Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

DOT	
UN number	UN1262
UN proper shipping name	Octanes, solution (Isooctane RQ = 1000 LBS), MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	• Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1262



**General information** 

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

## 15. Regulatory information

15. Regulatory informatio	11		
US federal regulations	This product is a "Hazardou Standard, 29 CFR 1910.120	s Chemical" as defined by the OSHA Haz 00.	ard Communication
TSCA Section 12(b) Export	Notification (40 CFR 707, Su	bpt. D)	
3,3',4,5-Tetrachlorobiphenyl (CAS 70362-49-1) CERCLA Hazardous Substance List (40 CFR 302.4)		0.00005 % Annual Export Notification	required.
Isooctane (CAS 540-84-		Listed.	
SARA 304 Emergency relea	ase notification		
	ed Substances (29 CFR 1910	.1001-1050)	
Not regulated.			
Superfund Amendments and Re	eauthorization Act of 1986 (S Immediate Hazard - Yes	ARA)	
Hazard categories	Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazar Not listed.	dous substance		
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutar	ts (HAPs) List	
Isooctane (CAS 540-84-	1)		
	n 112(r) Accidental Release F	Prevention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
US state regulations	WARNING: This product co birth defects or other reprod	ntains a chemical known to the State of C uctive harm.	alifornia to cause cancer and
US - California Proposi	tion 65 - CRT: Listed date/Ca	rcinogenic substance	
	biphenyl (CAS 70362-49-1)	Listed: October 1, 1989	
•	tion 65 - CRT: Listed date/De	•	
	biphenyl (CAS 70362-49-1) ate Chemicals List. Safer Cor	Listed: January 1, 1991 Isumer Products Regulations (Cal. Coc	de Regs, tit. 22, 69502.3,
Isooctane (CAS 540	9-84-1)		
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (AICS)	Yes
Canada	Domestic Substances List (I	DSL)	Yes
Canada	Non-Domestic Substances I	List (NDSL)	No
China	Inventory of Existing Chemic	cal Substances in China (IECSC)	Yes
Europe	European Inventory of Exist Substances (EINECS)	ing Commercial Chemical	Yes
Europe	European List of Notified Ch	emical Substances (ELINCS)	No
Japan	Inventory of Existing and Ne	w Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (EC	L)	Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

New Zealand Inventory

New Zealand

Philippines

No

Yes

#### Inventory name

#### United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date Revision date Version #	04-16-2014 08-12-2020 02
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
Disclaimer	Chem Service, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.
	Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.
	This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.
	Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.
Revision information	This product is furnished FOR LABORATORY USE ONLY. This document has undergone significant changes and should be reviewed in its entirety.