SAFETY DATA SHEET



1. Identification

Product identifier Volatiles Matrix Spike Mix-8260/CLP

Other means of identification

M-CLP5M4

For Laboratory Use Only Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Chem Service, Inc. 660 Tower Lane **Address**

West Chester, PA 19380

United States

Toll Free 800-452-9994 **Telephone** Direct 610-692-3026

Website www.chemservice.com E-mail info@chemservice.com

Chemtrec US 800-424-9300 **Emergency phone number**

Chemtrec outside US +1 703-527-3887

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 Health hazards Acute toxicity, oral Category 3 Acute toxicity, dermal Category 3 Acute toxicity, inhalation Category 3 Serious eye damage/eye irritation Category 2A Germ cell mutagenicity Category 1 Carcinogenicity Category 1A Reproductive toxicity (the unborn child) Category 2 Specific target organ toxicity, single exposure Category 1

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Specific target organ toxicity, repeated

Signal word Danger

Hazard statement Highly flammable liquid and vapor. Toxic if swallowed. Toxic in contact with skin. Causes serious

eye irritation. Toxic if inhaled. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs. Causes damage to organs through

Category 1

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear

protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Specific treatment (see this label). Rinse mouth. If eye irritation persists: Get medical

advice/attention. Take off immediately all contaminated clothing and wash it before reuse. In case

of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

0.5% of the mixture consists of component(s) of unknown acute oral toxicity. 0.9% of the mixture consists of component(s) of unknown acute dermal toxicity. 0.7% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	90 - 100
1,1-Dichloroethene		75-35-4	0.1
Benzene		71-43-2	0.1
Chlorobenzene		108-90-7	0.1
Toluene		108-88-3	0.1
Trichloroethene		79-01-6	0.1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. Get medical attention if irritation develops and

persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: Volatiles Matrix Spike Mix-8260/CLP

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Avoid contact with clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational expo	sure limits
-------------------	-------------

Components	Тур	oe .	V	alue
Benzene (CAS 71-43-2)	STE		5	ppm
	TW			ppm
US. OSHA Table Z-1 Lim		•	•	
Components	Тур	oe .	V	alue
Chlorobenzene (CAS	PEI	L	3	50 mg/m3
108-90-7)			7	Ennm
Methanol (CAS 67-56-1)	PEI			5 ppm 60 mg/m3
Wellianoi (CAS 07-50-1)	FEI	<u></u>		00 ppm
US. OSHA Table Z-2 (29	CFR 1910.1000)		2	оо ррпп
Components	Тур	oe .	V	alue
Benzene (CAS 71-43-2)	Cei	lina	2	5 ppm
Delizerie (OAO 7 1-40-2)	TW	•		o ppm
Toluene (CAS 108-88-3)	Cei			00 ppm
,	TW	•		00 ppm
Trichloroethene (CAS	Cei	ling		00 ppm
79-01-6)		_		
	TW	Ά	10	00 ppm
US. ACGIH Threshold Li				
Components	Тур	oe .	V	alue
1,1-Dichloroethene (CAS 75-35-4)	TW	'A	5	ppm
Benzene (CAS 71-43-2)	STE	EL	2	5 ppm
	TW	'A	0.	5 ppm
Chlorobenzene (CAS 108-90-7)	TW	Ά	10) ppm
Methanol (CAS 67-56-1)	STE			50 ppm
	TW			00 ppm
Toluene (CAS 108-88-3)	TW			0 ppm
Trichloroethene (CAS 79-01-6)	STI	= L	2	5 ppm
70010)	TW	'A	10	O ppm
US. NIOSH: Pocket Guid	e to Chemical Hazards	5		•
Components	Тур		V	alue
Benzene (CAS 71-43-2)	STI		1	ppm
Delizerie (OAO 7 1-40-2)	TW			1 ppm
Methanol (CAS 67-56-1)	STE			25 mg/m3
,	_			50 ppm
	TW	'A		60 mg/m3
			20	00 ppm
Toluene (CAS 108-88-3)	STE	EL	50	60 mg/m3
			1	50 ppm
	TW	'A	3	75 mg/m3
				00 ppm
Trichloroethene (CAS 79-01-6)	TW	Ά	29	5 ppm
ogical limit values				
ACGIH Biological Expos				
Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine ir urine	*

ACGIH Biological Expos Components	ure Indices Value	Determinant	Specimen	Sampling Time
Chlorobenzene (CAS 108-90-7)	100 mg/g	4-Chlorocatech ol, with hydrolysis	Creatinine in urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Trichloroethene (CAS 79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
·	0.5 mg/l	Trichloroethano I, without hydrolysis	Blood	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Benzene (CAS 71-43-2)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Skin designation applies.

Skin designation applies.

US - Tennesse OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear eye/face protection. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid

Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -144.04 °F (-97.8 °C) estimated Initial boiling point and boiling 148.46 °F (64.7 °C) estimated

range

Flash point 53.6 °F (12.0 °C) estimated

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

7.3 % estimated

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

169.3 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

867.2 °F (464 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

0.7881 g/cm3 estimated Density Flammability class Flammable IB estimated Percent volatile 99.5 % estimated 0.79 estimated Specific gravity VOC (Weight %) 99.5 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Toxic if swallowed.

Inhalation Toxic by inhalation. May cause damage to organs by inhalation.

Skin contact Toxic in contact with skin. Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Toxic by inhalation. Toxic if swallowed. Toxic in contact with skin. Expected to be a low hazard for

usual industrial or commercial handling by trained personnel.

Components **Species Test Results**

1,1-Dichloroethene (CAS 75-35-4)

Acute

Inhalation

LC50 Hamster, Chinese 1.8 mg/l

> 390 mg/m3, 22 Hours Mouse

> > 0.2 mg/l

Material name: Volatiles Matrix Spike Mix-8260/CLP

Components	Species	Test Results
	Rat	500 - 2500 ppm, 4 Hours
		8 mg/l
Oral		
LD50	Mouse	194 mg/kg
	Rat	80 mg/kg
Benzene (CAS 71-43-2)		
Acute		
Inhalation		
LC50	Mouse	9980 ppm
		9980 ppm, 7 Hours
	Rat	43767 mg/m3, 4 Hours
		13700 ppm, 4 Hours
		10000 ppm, 7 Hours
Oral		
LD50	Mouse	4700 mg/kg
	Rat	690 - 1230 mg/kg
Other	Maria	040
LD50	Mouse	340 mg/kg
		0.28 ml/kg
	Rat	2.89 mg/kg
Chlorobenzene (CAS 108-90	0-7)	
Acute		
<i>Inhalation</i> LC100	Mouse	0.05 mg/l
LC50	Mouse	1886 ppm, 6 Hours
2000	Rat	2965 ppm, 6 Hours
	Nut	13.9 mg/l, 6 Hours
Oral		10.5 mg/l, o riouis
LD50	Guinea pig	5060 mg/kg
	Mouse	778 mg/kg
	Rabbit	2250 mg/kg
	Rat	1110 mg/kg
		1.29 ml/kg
Other		11.25 Hilling
LD50	Mouse	515 mg/kg
	Rat	570 mg/kg
Methanol (CAS 67-56-1)		
Acute		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		64000 ppm, 4 Hours
		82.1 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	7300 mg/kg
	Pig	> 5000 mg/kg
	Rabbit	14.4 g/kg
	Rat	5628 mg/kg

Components	Species	Test Results
Other	O throat	0550 #
LD50	Guinea pig	3556 mg/kg
	Hamster	8555 mg/kg
	Mouse	4100 mg/kg
	Rabbit	1826 mg/kg
	Rat	2131 mg/kg
oluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
		14.1 ml/kg
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
		400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
		5879 - 6281 ppm, 6 Hours
		12.5 - 28.8 mg/l, 4 Hours
Oral		•
LD50	Rat	2.6 g/kg
Other		
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg
richloroethene (CAS 79-01-6)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Mouse	8450 ppm, 4 Hours
	Rat	26000 ppm, 1 Hours
		12000 ppm, 4 Hours
LD50	Mouse	49000 ppm, 30 Minutes
		5500 ppm, 10 Hours
NOEL	Guinea pig	730 mg/l
	Rabbit	730 mg/l
	Rat	730 mg/l
Oral	r tat	roo mg.
LD50	Mouse	2402 mg/kg
30	Rat	4920 mg/kg
Other		1020 mg/ng
LD100	Mouse	5500 mg/kg
LD50	Mouse	2402 mg/kg
LDUU		
	Rabbit	29 g/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,1-Dichloroethene (CAS 75-35-4) 3 Not classifiable as to carcinogenicity to humans.

Benzene (CAS 71-43-2) 1 Carcinogenic to humans.

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

Trichloroethene (CAS 79-01-6) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Benzene (CAS 71-43-2) Known To Be Human Carcinogen.

Trichloroethene (CAS 79-01-6) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2) Cancer

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity -

single exposure

Causes damage to organs.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 1,1-Dichloroethene (CAS 75-35-4) Aquatic Fish LC50 Bluegill (Lepomis macrochirus) 57 - 91 mg/l, 96 hours Benzene (CAS 71-43-2) Aquatic Crustacea EC50 Water flea (Daphnia magna) 8.76 - 15.6 mg/l, 48 hours Rainbow trout, donaldson trout Fish LC50 7.2 - 11.7 mg/l, 96 hours (Oncorhynchus mykiss) Chlorobenzene (CAS 108-90-7) Aquatic Fish LC50 Bluegill (Lepomis macrochirus) 4.1 - 4.9 mg/l, 96 hours Methanol (CAS 67-56-1) Aquatic EC50 > 10000 mg/l, 48 hours Crustacea Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours Fish Toluene (CAS 108-88-3) Aquatic Crustacea EC50 Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours LC50 Fish Coho salmon.silver salmon 8.11 mg/l, 96 hours (Oncorhynchus kisutch) Trichloroethene (CAS 79-01-6) Aquatic

Flagfish (Jordanella floridae)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanor water (log Now)	
1,1-Dichloroethene	2.13
Benzene	2.13
Chlorobenzene	2.89
Methanol	-0.77
Toluene	2.73

LC50

Fish

3.1 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

2.61 Trichloroethene

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

> and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

US RCRA Hazardous Waste U List: Reference

1,1-Dichloroethene (CAS 75-35-4) U078 Benzene (CAS 71-43-2) U019 Chlorobenzene (CAS 108-90-7) U037 Methanol (CAS 67-56-1) U154 Toluene (CAS 108-88-3) U220 Trichloroethene (CAS 79-01-6) 11228

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN1230 **UN number**

UN proper shipping name Methanol, solution

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Ш **Packing group**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB2, T7, TP2 Special provisions

Packaging exceptions 150 Packaging non bulk 202 Packaging bulk 242

IATA

UN1230 **UN number**

UN proper shipping name Transport hazard class(es) Methanol solution

Class 3

6.1(PGI, II) Subsidiary risk

Ш **Packing group**

Environmental hazards No. **ERG Code** 31

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Other information

Allowed.

Cargo aircraft only

Allowed.

IMDG

IIN number UN1230

UN proper shipping name Transport hazard class(es) METHANOL SOLUTION

Class 3

Subsidiary risk 6.1(PGI, II)

Packing group

Material name: Volatiles Matrix Spike Mix-8260/CLP

Environmental hazards

Marine pollutant No. EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not available.

the IBC Code





IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,1-Dichloroethene (CAS 75-35-4)Listed.Benzene (CAS 71-43-2)Listed.Chlorobenzene (CAS 108-90-7)Listed.Methanol (CAS 67-56-1)Listed.Toluene (CAS 108-88-3)Listed.Trichloroethene (CAS 79-01-6)Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2) Cancer

Central nervous system

Blood Aspiration Skin Eye

respiratory tract irritation

Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Methanol	67-56-1	90 - 100	
Benzene	71-43-2	0.1	
Trichloroethene	79-01-6	0.1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,1-Dichloroethene (CAS 75-35-4)

Benzene (CAS 71-43-2)

Chlorobenzene (CAS 108-90-7)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Trichloroethene (CAS 79-01-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Dichloroethene (CAS 75-35-4)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

1,1-Dichloroethene (CAS 75-35-4)

Benzene (CAS 71-43-2)

Chlorobenzene (CAS 108-90-7)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Trichloroethene (CAS 79-01-6)

US. New Jersey Worker and Community Right-to-Know Act

1,1-Dichloroethene (CAS 75-35-4)	500 LBS
Benzene (CAS 71-43-2)	500 LBS
Chlorobenzene (CAS 108-90-7)	500 LBS
Methanol (CAS 67-56-1)	500 LBS
Toluene (CAS 108-88-3)	500 LBS
Trichloroethene (CAS 79-01-6)	500 LBS

US. Pennsylvania RTK - Hazardous Substances

1,1-Dichloroethene (CAS 75-35-4)

Benzene (CAS 71-43-2)

Chlorobenzene (CAS 108-90-7)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Trichloroethene (CAS 79-01-6)

US. Rhode Island RTK

1,1-Dichloroethene (CAS 75-35-4)

Benzene (CAS 71-43-2)

Chlorobenzene (CAS 108-90-7)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Trichloroethene (CAS 79-01-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Trichloroethene (CAS 79-01-6) Listed: April 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

 Benzene (CAS 71-43-2)
 Listed: December 26, 1997

 Methanol (CAS 67-56-1)
 Listed: March 16, 2012

 Toluene (CAS 108-88-3)
 Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-29-2014

Version #

Health: 2 NFPA ratings

Flammability: 3 Instability: 0

Disclaimer

The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.

Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.

197 Version #: 01 Issue date: 08-29-2014