

SAFETY DATA SHEET

1. Identification

Product identifier	Labeled Compounds Spiking	Mixture - 1666	
Other means of identification			
Item	M-LCS16661M99		
Recommended use	For Laboratory Use Only		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/I	Distributor information		
Manufacturer			
Company name	Chem Service, Inc.		
Address	660 Tower Lane		
	West Chester, PA 19380		
	United States		
Telephone	Toll Free	800-452-9994	
·	Direct	610-692-3026	
Website	www.chemservice.com		
E-mail	info@chemservice.com		
Emergency phone number	Chemtrec US	800-424-9300	
	Chemtrec outside US	+1 703-527-38	87
2. Hazard(s) identification			
Physical hazards	Flammable liquids		Category 2
•			
Health hazards	Acute toxicity, oral		Category 3
	Acute toxicity, dermal		Category 3
	Acute toxicity, inhalation		Category 3
	Serious eye damage/eye irritati	on	Category 2A

 Reproductive toxicity

 Specific target organ toxicity, single exposure

 Specific target organ toxicity, repeated exposure

 Environmental hazards
 Not classified.

 OSHA defined hazards
 Not classified.

Label elements



Signal word Hazard statement

Response

Precautionary statement Prevention Highly flammable liquid and vapor. Toxic if swallowed. Toxic in contact with skin. Causes serious eye irritation. Toxic if inhaled. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Category 2

Category 1

Category 1

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Specific treatment (see this label). Rinse mouth. If eye irritation persists: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	1% of the mixture consists of component(s) of unknown acute oral toxicity. 1% of the mixture consists of component(s) of unknown acute dermal toxicity. 1% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	90 - 100
tert-Butyl alcohol-d10		53001-22-2	0.025
Cyclohexane-d12		1735-17-7	0.0025
Ethyl acetate-13C2		84508-45-2	0.0025
n-Heptane-d16		33838-52-7	0.0025
n-Hexane-d14		21666-38-6	0.0025
o-Xylene-d10		56004-61-6	0.0025
p-Xylene-d10		41051-88-1	0.0025
Tetrahydrofuran-d8		1693-74-9	0.0025

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapor.
General file hazarus	

6. Accidental release measures

6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Avoid contact with clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.
8 Exposure controls/perso	onal protection

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3

		Туре	Va	
			20	00 ppm
US. ACGIH Threshold Lin Components		Туре	V	alue
		Туре		
Methanol (CAS 67-56-1)		STEL TWA		50 ppm 30 ppm
US. NIOSH: Pocket Guide			20	yo bhili
Components		Туре	V	alue
Methanol (CAS 67-56-1)		STEL		25 mg/m3
				50 ppm
		TWA		60 mg/m3
			20)0 ppm
ological limit values				
ACGIH Biological Exposu			Chaoline ar	Somaling Time
Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
* - For sampling details, ple	ease see the source	e document.		
posure guidelines				
US - California OELs: Ski	•	_		
Methanol (CAS 67-56- US - Minnesota Haz Subs			be absorbed throu	ugh the skin.
Methanol (CAS 67-56-	•	Skin	designation appli	es.
US - Tennesse OELs: Ski	•	Cont	a abaarbad thra	igh the ekin
Methanol (CAS 67-56- US ACGIH Threshold Lim	•		be absorbed throu	
Methanol (CAS 67-56-	•		be absorbed throu	ugh the skin.
•	to Chamical Haran			
US NIOSH Pocket Guide		-		
US NIOSH Pocket Guide Methanol (CAS 67-56-	1)	Can b	be absorbed through	-
US NIOSH Pocket Guide	1) Explosion-proc changes per h applicable, use maintain airbor	Can b of general and local ext our) should be used. V process enclosures, h rne levels below recom	naust ventilation. entilation rates sl ocal exhaust ven mended exposu	ugh the skin. Good general ventilation (typically 10 ai hould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station.
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols	1) Explosion-proc changes per h applicable, use maintain airbon established, m	Can b of general and local ext our) should be used. V process enclosures, l rne levels below recom aintain airborne levels nal protective equipm	naust ventilation. entilation rates sl ocal exhaust ven imended exposui to an acceptable ent	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station.
US NIOSH Pocket Guide to Methanol (CAS 67-56- propriate engineering ntrols	1) Explosion-proc changes per h applicable, use maintain airbon established, m	Can b of general and local ext our) should be used. V process enclosures, l rne levels below recom aintain airborne levels nal protective equipm	naust ventilation. entilation rates sl ocal exhaust ven imended exposui to an acceptable ent	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols	1) Explosion-proc changes per h applicable, use maintain airbou established, m es, such as persor Wear eye/face	Can be of general and local ext our) should be used. V e process enclosures, le rne levels below recom aintain airborne levels nal protective equipm protection. Wear safet	naust ventilation. entilation rates sl ocal exhaust ven imended exposui to an acceptable ent	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station.
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols	1) Explosion-proc changes per h applicable, use maintain airbon established, m	Can be of general and local ext our) should be used. V e process enclosures, le rne levels below recom aintain airborne levels nal protective equipm protection. Wear safet	naust ventilation. entilation rates sl ocal exhaust ven imended exposui to an acceptable ent	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station.
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols	1) Explosion-proc changes per h- applicable, use maintain airbou established, m es, such as persor Wear eye/face Wear protectiv	Can be of general and local ext our) should be used. V e process enclosures, le rne levels below recom aintain airborne levels nal protective equipm protection. Wear safet	naust ventilation. entilation rates sl ocal exhaust ven imended exposu to an acceptable ent ty glasses with si	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station.
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols lividual protection measure Eye/face protection Skin protection Hand protection	1) Explosion-proc changes per h applicable, use maintain airbou established, m es, such as persor Wear eye/face Wear protectiv Wear appropria If engineering limits (where a	Can b of general and local ext our) should be used. V e process enclosures, le rne levels below recom aintain airborne levels hal protective equipm protection. Wear safet re gloves. ate chemical resistant of controls do not maintai	naust ventilation. entilation rates sl ocal exhaust ven imended exposur to an acceptable ent ty glasses with si clothing. n airborne conce eptable level (in c	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not beer level. Provide eyewash station. de shields (or goggles).
US NIOSH Pocket Guide f Methanol (CAS 67-56- propriate engineering ntrols lividual protection measure Eye/face protection Skin protection Hand protection Other	1) Explosion-proc changes per h applicable, use maintain airbon established, m es, such as persor Wear eye/face Wear protectiv Wear appropria If engineering limits (where a been establish	Can b of general and local ext our) should be used. V e process enclosures, le rne levels below recom aintain airborne levels hal protective equipm protection. Wear safet re gloves. ate chemical resistant of controls do not maintai pplicable) or to an acce	naust ventilation. entilation rates sl ocal exhaust ven imended exposui to an acceptable ent ty glasses with si clothing. n airborne conce eptable level (in o rator must be wo	Good general ventilation (typically 10 ai nould be matched to conditions. If tilation, or other engineering controls to e limits. If exposure limits have not beer level. Provide eyewash station. de shields (or goggles). ntrations below recommended exposure countries where exposure limits have nor rn.

Appearance	
Physical state	Liquid.
Form	Liquid
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.

Melting point/freezing point	-144.04 °F (-97.8 °C) estimated
Initial boiling point and boiling range	148.46 °F (64.7 °C) estimated
Flash point	53.6 °F (12.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	7.3 % estimated
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	169.3 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	867.2 °F (464 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.7865 g/cm3 estimated
Flammability class	Flammable IB estimated
Percent volatile	99 % estimated
Specific gravity	0.79 estimated
VOC (Weight %)	99 % estimated
10 Stability and reactivity	

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Toxic if swallowed.
Inhalation	Toxic by inhalation. May cause damage to organs by inhalation.
Skin contact	Toxic in contact with skin.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Toxic by inhalation. Toxic if swallowed. Toxic in contact with skin. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results		
Methanol (CAS 67-56-1)				
Acute				
Dermal		15000		
LD50	Rabbit	15800 mg/kg		
Inhalation LC50	Mouse	79.43 mg/l, 134 Minutes		
2030	Rat	> 115.9 mg/l, 4 Hours		
	Nat	64000 ppm, 4 Hours		
		82.1 mg/l, 6 Hours		
Oral		oz. r mg/l, o nours		
LD50	Monkey	6000 mg/kg		
2000	Mouse	7300 mg/kg		
	Pig	> 5000 mg/kg		
	Rabbit	14.4 g/kg		
	Rat	5628 mg/kg		
Other		00 <u>2</u> 0gg		
LD50	Guinea pig	3556 mg/kg		
	Hamster	8555 mg/kg		
	Mouse	4100 mg/kg		
	Rabbit	1826 mg/kg		
	Rat	2131 mg/kg		
* Estimates for product may b	e based on additional component data	not shown.		
Skin corrosion/irritation	Prolonged skin contact may cause te	emporary irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.			
Respiratory or skin sensitization				
Respiratory sensitization	Not available.			
Skin sensitization	This product is not expected to caus			
Germ cell mutagenicity	No data available to indicate product mutagenic or genotoxic.	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
US. OSHA Specifically Regu	lated Substances (29 CFR 1910.100	1-1050)		
Not listed.				
Reproductive toxicity	Suspected of damaging fertility or th	e unborn child.		
Specific target organ toxicity - single exposure	Causes damage to organs.			
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.			
Aspiration hazard	Not available.			
Chronic effects	Prolonged inhalation may be harmfu exposure.	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure.		
12. Ecological information	1			
Ecotoxicity		ronmentally hazardous. However, this does not exclude the s can have a harmful or damaging effect on the environment.		
Components	Species	Test Results		
Mathemal (CAC CZ EC 1)				

Components		Species	Test Results
Methanol (CAS 67-	56-1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales pron	nelas) >100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)		
Methanol	-0.77	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
US RCRA Hazardous Waste U List: Reference			
Methanol (CAS 67-56-1)	U154		

(
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.


14. Transport information

_	-		
n	ſ	٦	
	5		

DOT	
UN number	UN1230
UN proper shipping name	Methanol, solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP2
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1230
UN proper shipping name	Methanol solution
Transport hazard class(es)	
Class	3
Subsidiary risk	6.1(PGI, II)
Packing group	Ш
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1230
UN proper shipping name	METHANOL SOLUTION
Transport hazard class(es)	
Class	3
Subsidiary risk	6.1(PGI, II)
Packing group	Ш
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
-	

Transport in bulk according toNot available.Annex II of MARPOL 73/78 andthe IBC Code

DOT



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.

	one of more componente are		•	
TSCA Section 12(b) Export N	lotification (40 CFR 707, Sub	pt. D)		
Not regulated.	-			
CERCLA Hazardous Substar	nce List (40 CFR 302.4)			
Methanol (CAS 67-56-1)		Listed.		
SARA 304 Emergency releas	e notification			
Not regulated.				
US. OSHA Specifically Regu	lated Substances (29 CFR 19	10.1001-1050)		
Not listed.				
Superfund Amendments and Rea	authorization Act of 1986 (SA	RA)		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	,		
SARA 302 Extremely hazard	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Methanol		67-56-1	90 - 100	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants	s (HAPs) List		
Methanol (CAS 67-56-1)	112(r) Accidental Release Pr		68.130)	
Not regulated.				
Safe Drinking Water Act				
(SDWA)	Not regulated.			
-	Not regulated.			
(SDWA)				
(SDWA) US state regulations				

US. New Jersey Worker and	Community Right-to-Know Act	
Methanol (CAS 67-56-1)	500 LBS	
US. Pennsylvania RTK - Haz	ardous Substances	
Methanol (CAS 67-56-1) US. Rhode Island RTK		
Methanol (CAS 67-56-1)		
US. California Proposition 6	5	
	contains a chemical known to the State of California to cause birth defec	cts or other reproductive
	ion 65 - CRT: Listed date/Developmental toxin	
Methanol (CAS 67-5	6-1) Listed: March 16, 2012	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No
	nents of this product comply with the inventory requirements administered by the components of the product are not listed or exempt from listing on the inventory	
16. Other information, incl	uding date of preparation or last revision	
Issue date	08-15-2014	
Version #	01	
NFPA ratings	Health: 2 Flammability: 3 Instability: 0	
Disclaimer	The above information is believed to be correct on the date it was last considered all inclusive. The information has been obtained only by a s and is only a guide for handling the chemicals. OSHA regulations requ become evident, an upgraded SDS must be made available to the emp RESPONSIBILITY for updates lies with the employer and not with CHE	search of available literature ire that if other hazards ployee within three months.
	Persons not specifically and properly trained should not handle this ch product is furnished FOR LABORATORY USE ONLY! Our products m cosmetics, agricultural or pesticide products, food additives or as hous	ay NOT BE USED as drugs,

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.