# SAFETY DATA SHEET



#### 1. Identification

Product identifier Florida Total Petroleum Hydrocarbon Standards Mixture - TPH

Other means of identification

Item M-TPH7J3

Recommended use For Laboratory Use Only

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

**Company name**Chem Service, Inc.
Address
660 Tower Lane

West Chester, PA 19380

**United States** 

**Telephone** Toll Free 800-452-9994

Direct 610-692-3026

Website www.chemservice.com

E-mail info@chemservice.com

**Emergency phone number** Chemtrec US 800-424-9300

Chemtrec outside US +1 703-527-3887

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 2Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Reproductive toxicity (fertility)

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Highly flammable liquid and vapor. Fatal if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Causes damage to

organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with

Category 2

Category 1

Category 2

long lasting effects.

#### **Precautionary statement**

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

## Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

# Disposal

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

0.8% of the mixture consists of component(s) of unknown acute oral toxicity. 0.95% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 0.9% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
n-Hexane		110-54-3	99.15
n-Decane		124-18-5	0.05
n-Docosane		629-97-0	0.05
n-Dodecane		112-40-3	0.05
n-Dotriacontane		544-85-4	0.05
n-Eicosane		112-95-8	0.05
n-Hexacosane		630-01-3	0.05
n-Hexadecane		544-76-3	0.05
n-Hexatriacontane		630-06-8	0.05
n-Octacosane		630-02-4	0.05
n-Octadecane		593-45-3	0.05
n-Octane		111-65-9	0.05
n-Octatriacontane		7194-85-6	0.05
n-Tetracontane		4181-95-7	0.05
n-Tetracosane		646-31-1	0.05
n-Tetradecane		629-59-4	0.05
n-Tetratriacontane		14167-59-0	0.05
n-Triacontane		638-68-6	0.05

# 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

**Skin contact**Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

## Ingestion

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

the chemical

Specific hazards arising from

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods
General fire hazards

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

# **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

## 8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

## Occupational exposure limits

Components	Туре	Value	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
n-Octane (CAS 111-65-9)	PEL	2350 mg/m3	
,		500 ppm	
<b>US. ACGIH Threshold Limit Value</b>	es		
Components	Type	Value	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
n-Octane (CAS 111-65-9)	TWA	300 ppm	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
_	_		

US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value		
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3		
		50 ppm		
n-Octane (CAS 111-65-9)	Ceiling	1800 mg/m3		
		385 ppm		
	TWA	350 mg/m3		
		75 ppm		

#### **Biological limit values**

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid

ColorNot available.OdorNot available.Odor thresholdNot available.pHNot available.

Melting point/freezing point -137.74 °F (-94.3 °C) estimated Initial boiling point and boiling 155.66 °F (68.7 °C) estimated

range

Flash point -7.0 °F (-21.7 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 202.64 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 437 °F (225 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 0.74264 g/cm3 estimated

Flammability class Flammable IB estimated

Specific gravity 0.74 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Prolonged inhalation may be harmful. May cause damage to organs by inhalation.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Fatal if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### Information on toxicological effects

Acute toxicity Fatal if swallowed. Narcotic effects. Expected to be a low hazard for usual industrial or

commercial handling by trained personnel.

commercial handling by trained personnel.			
Components	Species	Test Results	
n-Decane (CAS 124-18-5)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	>= 3160 mg/kg, 24 Hours	
	Rat	> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Monkey	>= 11160 mg/m3	
	Mouse	72.3 mg/l, 2 Hours	
Vapor			
LC50	Rat	> 5000 mg/m3, 8 Hours	
		> 4951 mg/m3, 4 Hours	
		> 41 ppm, 8 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
n-Dodecane (CAS 112-40-3	3)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	>= 3160 mg/kg, 24 Hours	
	Rat	> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Monkey	>= 11160 mg/m3	
Vapor			
LC50	Rat	> 5000 mg/m3, 8 Hours	
		> 4951 mg/m3, 4 Hours	

Components	Species	Test Results
		> 41 ppm, 8 Hours
Oral	_	
LD50	Rat	> 5000 mg/kg
n-Eicosane (CAS 112-95-8)		
<u>Acute</u> Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
Aerosol		
LC50	Rat	> 5266 mg/m3, 4 Hours
n-Hexadecane (CAS 544-76-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
Aerosol	Det	5000 may/m2 4 Haven
LC50	Rat	> 5266 mg/m3, 4 Hours
n-Hexane (CAS 110-54-3)		
<u>Acute</u> Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 5 ml/kg
Inhalation		- Thung
LC50	Mouse	48000 ppm, 4 Hours
	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral		rocco pp.m, Triodic
LD50	Rat	24 ml/kg
		24 mg/kg
	Wistar rat	49 mg/kg
n-Octadecane (CAS 593-45-3)		3 3
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
Aerosol		
LC50	Rat	> 5266 mg/m3, 4 Hours
n-Octane (CAS 111-65-9)		
Acute Dormol		
<b>Dermal</b> LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation	Napoli	- 2000 Hig/kg, 27 Houls
Vapor		
LC50	Rat	> 24.88 mg/l, 4 Hours

Components	Species	Test Results
Oral		
LD50	Rat	> 5000 mg/kg
n-Tetradecane (CAS 629-5	59-4)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	>= 3160 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Monkey	>= 11160 mg/m3
Vapor		
LC50	Rat	> 5000 mg/m3, 8 Hours
		> 4951 mg/m3, 4 Hours
		> 41 ppm, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure.

# 12. Ecological information

**Ecotoxicity**Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components		Species	Test Results
n-Decane (CAS 124	-18-5)		
Aquatic			
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 500 mg/l, 96 hours
n-Docosane (CAS 6	29-97-0)		
Aquatic			
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 500 mg/l, 96 hours

Components Species Test Results

n-Hexane (CAS 110-54-3)

**Aquatic** 

Fish LC50 Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 n-Decane
 5.01

 n-Hexadecane
 8.25

 n-Hexane
 3.9

 n-Octane
 5.18

 n-Tetradecane
 7.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

#### 14. Transport information

DOT

UN number UN1208

**UN proper shipping name** Hexanes, solution (n-Hexane RQ = 5043 LBS)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

**IATA** 

UN number UN1208

**UN proper shipping name** Hexanes solution (n-Hexane)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed.

**IMDG** 

**UN** number UN1208

**UN** proper shipping name **HEXANES SOLUTION (n-Hexane)** 

Allowed.

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш

**Environmental hazards** 

Marine pollutant No. F-E, S-D **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



**General information** DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

n-Hexane (CAS 110-54-3) Listed. n-Octane (CAS 111-65-9) Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
n-Hexane	110-54-3	99.15	

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act** 

Not regulated.

(SDWA)

#### **US** state regulations

#### US - New Jersey RTK - Substances: Listed substance

n-Decane (CAS 124-18-5)

n-Hexane (CAS 110-54-3)

n-Octane (CAS 111-65-9)

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

n-Hexane (CAS 110-54-3)

#### **US. Massachusetts RTK - Substance List**

n-Hexane (CAS 110-54-3)

n-Octane (CAS 111-65-9)

#### US. New Jersey Worker and Community Right-to-Know Act

n-Hexane (CAS 110-54-3)

#### US. Pennsylvania RTK - Hazardous Substances

n-Decane (CAS 124-18-5)

n-Hexane (CAS 110-54-3)

n-Octane (CAS 111-65-9)

#### US. Pennsylvania Worker and Community Right-to-Know Law

n-Decane (CAS 124-18-5)

n-Hexane (CAS 110-54-3)

n-Octane (CAS 111-65-9)

#### **US. Rhode Island RTK**

n-Hexane (CAS 110-54-3)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region Inventory name On inventory (yes/no)\*

Japan Inventory of Existing and New Chemical Substances (ENCS) No

Korea Existing Chemicals List (ECL)

New ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesNo

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 05-02-2014

 Revision date
 09-07-2016

Version # 02

NFPA ratings Health: 4

Flammability: 3 Instability: 0

Disclaimer

The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.

Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.

Revision Information Composition / Information on Ingredients: Ingredients