

SAFETY DATA SHEET

1. Identification

Product identifier	o-Terphenyl Solution		
Other means of identification			
Item	S-12693B5		
Recommended use	For Laboratory Use Only		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier	Distributor information		
Manufacturer			
Company name Address	Chem Service, Inc. 660 Tower Lane West Chester, PA 19380 United States		
Telephone	Toll Free	800-452-9994	
	Direct	610-692-3026	3
Website	www.chemservice.com		
E-mail	info@chemservice.com		
Emergency phone number	Chemtrec US Chemtrec outside US	800-424-9300 +1 703-527-38	
	Chemilec buiside 03	+1703-327-30	507
2. Hazard(s) identification			
Physical hazards	Flammable liquids		Category 2
lealth hazards	Acute toxicity, dermal		Category 1
	Serious eye damage/eye irritati	ion	Category 2A
	Specific target organ toxicity, si	ingle exposure	Category 3 narcotic effects
Environmental hazards	Hazardous to the aquatic environment, acute hazard		Category 3
	Hazardous to the aquatic environment	onment,	Category 3
	long-term hazard		

OSHA defined hazards

Label elements



	• •
Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Fatal in contact with skin. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing. Wear protective gloves/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see this label). If eye irritation persists: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

0.2% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 0.2% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	>99
o-Terphenyl		84-15-1	0.2

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Discard any shoes or clothing items that cannot be decontaminated.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.
6. Accidental release meas	sures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not taste or swallow. Avoid breathing mist or vapor. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
o-Terphenyl (CAS 84-15-1)	Ceiling	9 mg/m3	
		1 ppm	
US. ACGIH Threshold Limit Values	6		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
o-Terphenyl (CAS 84-15-1)	Ceiling	5 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
o-Terphenyl (CAS 84-15-1)	Ceiling	5 mg/m3	
		0.5 ppm	

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
* - For sampling details, p	ease see the source	e document.		
Appropriate engineering controls	changes per h applicable, us maintain airbo	our) should be used. Ve e process enclosures, lo rne levels below recom	entilation rates sh ocal exhaust vent mended exposur	Good general ventilation (typically 10 air nould be matched to conditions. If tilation, or other engineering controls to e limits. If exposure limits have not been level. Provide eyewash station.
ndividual protection measu	res, such as perso	nal protective equipme	ent	
Eye/face protection	Wear eye/face	e protection. Wear safety	y glasses with sid	de shields (or goggles).
Skin protection				
Hand protection	Wear protectiv	ve gloves.		
Other	Wear appropri	ate chemical resistant c	lothing.	
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.			
Thermal hazards	Wear appropri	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	personal hygie	ene measures, such as	washing after ha	s material on clothing. Always observe go ndling the material and before eating, g and protective equipment to remove

9. Physical and chemical properties

-	-
Appearance	
Physical state	Liquid.
Form	Liquid
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-138.46 °F (-94.7 °C) estimated
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-4.0 °F (-20.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	308.63 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	869 °F (465 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.79042 g/cm3 estimated

Flammability class	Flammable IB estimated
Percent volatile	99.8 % estimated
Specific gravity	0.79 estimated
VOC (Weight %)	99.8 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.	
Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.	
Skin contact	Fatal in contact with skin.	
Eye contact	Causes serious eye irritation.	
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	

Information on toxicological effects

Acute toxicity

Fatal in contact with skin. Narcotic effects. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20 mg/kg
		20 ml/kg
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		76 mg/l, 4 Hours
		50.1 mg/l
		50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
		2.2 ml/kg
Other		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
o-Terphenyl (CAS 84-15-1)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	> 3.8 mg/l, 4 Hours

Components	Species		Test Results	
Oral				
LD50	Rat		2304 mg/kg	
* Estimates for product may b	e based on a	dditional component data not shown.		
Skin corrosion/irritation	Prolonged :	skin contact may cause temporary irritat	ion.	
Serious eye damage/eye irritation	Causes ser	ious eye irritation.		
Respiratory or skin sensitization	n			
Respiratory sensitization	Not available.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
US. OSHA Specifically Reg	ulated Substa	ances (29 CFR 1910.1001-1050)		
Not listed.				
Reproductive toxicity	This produc	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Narcotic eff	fects.		
Specific target organ toxicity - repeated exposure	Not classifie	ed.		
Aspiration hazard	Not availab	le.		
Chronic effects	Prolonged i	inhalation may be harmful.		
12 Ecological information	-			
12. Ecological information				
Ecotoxicity	Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.			
Components		Species	Test Results	
Acetone (CAS 67-64-1)				
Aquatic	5050		04.0.00.0 mmm// 40 hours	
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
* Estimates for product may b	e based on a	dditional component data not shown.		
Persistence and degradability	No data is a	available on the degradability of this prod	duct.	
Bioaccumulative potential	No data ava	ailable.		
Partition coefficient n-octar Acetone	iol / water (lo	-0.24		
Mobility in soil	No data ava			
-			e depletion, photochemical ozone creation ential) are expected from this component.	
Other adverse effects	potential, e			
13. Disposal consideratio	•			
13. Disposal consideratio	ns Collect and and its cont sewers/wat	reclaim or dispose in sealed containers tainer must be disposed of as hazardous er supplies. Do not contaminate ponds, Dispose of contents/container in accorda	at licensed waste disposal site. This materia s waste. Do not allow this material to drain int waterways or ditches with chemical or used ince with local/regional/national/international	
	ns Collect and and its cont sewers/wat container. I regulations	reclaim or dispose in sealed containers tainer must be disposed of as hazardous er supplies. Do not contaminate ponds, Dispose of contents/container in accorda	s waste. Do not allow this material to drain int waterways or ditches with chemical or used unce with local/regional/national/international	

disposal company.			
US RCRA Hazardous Waste U List: Reference			
Acetone (CAS 67-64-1)	U002		

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

DOT	
UN number	UN1090
UN proper shipping name	Acetone, solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
IATA	
UN number	UN1090
UN proper shipping name	Acetone solution
Transport hazard class(es)	
Class	3
	5
Subsidiary risk Packing group	-
Environmental hazards	No.
ERG Code	NO. 3H
	Read safety instructions, SDS and emergency procedures before handling.
Other information	Read salety instructions, SDS and emergency procedures before handling.
	Allowed
Passenger and cargo aircraft	Allowed.
	Allowed.
Cargo aircraft only IMDG	Allowed.
UN number	
UN proper shipping name	ACETONE (ACETONE SOLUTIONS)
Transport hazard class(es)	_
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
· · ·	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	
FLAMMABLE 3	

IATA; IMDG



15. Regulatory information

15. Regulatory information			
US federal regulations	This product is a "Hazardous Standard, 29 CFR 1910.1200 All components are on the U.S		Communication
TSCA Section 12(b) Expor	t Notification (40 CFR 707, Sub	pt. D)	
Not regulated. CERCLA Hazardous Subst	tance List (40 CFR 302.4)		
Acetone (CAS 67-64-1)		Listed.	
SARA 304 Emergency rele Not regulated.			
•	gulated Substances (29 CFR 19	10.1001-1050)	
	Reauthorization Act of 1986 (SA	RA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	,	
SARA 302 Extremely haza Not listed.	rdous substance		
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section	on 112 Hazardous Air Pollutants	s (HAPs) List	
	on 112(r) Accidental Release Pr	evention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Ad Chemical Code Numb		ential Chemicals (21 CFR 1310.02(b) and 1	l310.04(f)(2) and
Acetone (CAS 67-6 Drug Enforcement Ad	,	6532 xempt Chemical Mixtures (21 CFR 1310.1	2(c))
Acetone (CAS 67-6 DEA Exempt Chemica	64-1) I Mixtures Code Number	35 %WV	
Acetone (CAS 67-6	j4-1)	6532	
US state regulations			
US. Massachusetts RTK -	Substance List		
Acetone (CAS 67-64-1) o-Terphenyl (CAS 84-1	5-1)		
-	nd Community Right-to-Know A	ict	
Not regulated. US. Pennsylvania RTK - Ha			
Acetone (CAS 67-64-1) o-Terphenyl (CAS 84-1 US. Rhode Island RTK			
Acetone (CAS 67-64-1)			
		ct of 1986 (Proposition 65): This material is r ctive toxins.	not known to contain
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Chemi		Yes
Canada	Domestic Substances List (DS		Yes
Canada	Non-Domestic Substances Lis		No
China	Inventory of Existing Chemica	al Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-31-2014
Version #	01
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
Disclaimer	The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.
	Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.
	This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.
	Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.
	This product is furnished FOR LABORATORY USE ONLY.