

**1. Identification**

|   |   |                 |
|---|---|-----------------|
| <b>Product identifier</b>                                     | <b>Benzo(a)pyrene-d12 Solution</b>                        |                 |
| <b>Other means of identification</b>                          |   |                 |
| Item  | S-14039K1   |                 |
| <b>Recommended use</b>  | For Laboratory Use Only                                   |                 |
| <b>Recommended restrictions</b>                               | None known.   |                 |
| <b>Manufacturer/Importer/Supplier/Distributor information</b> |   |                 |
| <b>Manufacturer</b>   |   |                 |
| <b>Company name</b>   | Chem Service, Inc.  |                 |
| <b>Address</b>  | 660 Tower Lane<br>West Chester, PA 19380<br>United States |                 |
| <b>Telephone</b>  | Toll Free   | 800-452-9994    |
|   | Direct  | 610-692-3026    |
| <b>Website</b>  | www.chemservice.com                                       |                 |
| <b>E-mail</b>   | info@chemservice.com                                      |                 |
| <b>Emergency phone number</b>                                 | Chemtec US  | 800-424-9300    |
|   | Chemtec outside US  | +1 703-527-3887 |

**2. Hazard(s) identification**

|                              |  |                             |
|------------------------------|--|-----------------------------|
| <b>Physical hazards</b>      | Flammable liquids                                      | Category 2                  |
| <b>Health hazards</b>        | Skin corrosion/irritation                              | Category 2                  |
|                              | Specific target organ toxicity, single exposure        | Category 3 narcotic effects |
|                              | Aspiration hazard                                      | Category 1                  |
| <b>Environmental hazards</b> | Hazardous to the aquatic environment, acute hazard     | Category 1                  |
|                              | Hazardous to the aquatic environment, long-term hazard | Category 1                  |
| <b>OSHA defined hazards</b>  | Not classified.  |                             |

**Label elements**

|                                |  |
|--------------------------------|--|
| <b>Signal word</b>             | Danger   |
| <b>Hazard statement</b>        | Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.  |
| <b>Precautionary statement</b> |  |
| <b>Prevention</b>              | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face protection. |
| <b>Response</b>                | If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.       |
| <b>Storage</b>                 | Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.   |

|  |   |
|--|---|
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national/international regulations.   |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.                   |
| <b>Supplemental information</b>                  | 0.01% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 0.01% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name      | Common name and synonyms | CAS number | %     |
|--------------------|--------------------------|------------|-------|
| Isooctane          | 2,2,4-Trimethylpentane   | 540-84-1   | 99.99 |
| Benzo(a)pyrene-d12 |                          | 63466-71-1 | 0.01  |

### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.   |
| <b>Skin contact</b>   | Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.   |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.   |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.   |
| <b>Most important symptoms/effects, acute and delayed</b>                     | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.   |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed. |
| <b>General information</b>  | Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.   |

### 5. Fire-fighting measures

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.  |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.   |
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.  |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.   |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials.   |
| <b>General fire hazards</b>  | Highly flammable liquid and vapor.   |

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components               | Type | Value                             |
|--------------------------|------|-----------------------------------|
| Isooctane (CAS 540-84-1) | PEL  | 2350 mg/m <sup>3</sup><br>500 ppm |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components               | Type    | Value                  |
|--------------------------|---------|------------------------|
| Isooctane (CAS 540-84-1) | Ceiling | 1800 mg/m <sup>3</sup> |
|                          |         | 385 ppm                |
|                          | TWA     | 350 mg/m <sup>3</sup>  |
|                          |         | 75 ppm                 |

|  |   |
|--|---|
| <b>Biological limit values</b>   | No biological exposure limits noted for the ingredient(s).  |
| <b>Appropriate engineering controls</b>                                      | Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. |
| <b>Individual protection measures, such as personal protective equipment</b> |   |
| <b>Eye/face protection</b>   | Chemical respirator with organic vapor cartridge and full facepiece.  |
| <b>Skin protection</b>   |   |
| <b>Hand protection</b>   | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.   |
| <b>Other</b>   | Wear appropriate chemical resistant clothing.   |
| <b>Respiratory protection</b>  | Chemical respirator with organic vapor cartridge and full facepiece.  |
| <b>Thermal hazards</b>   | Wear appropriate thermal protective clothing, when necessary.   |
| <b>General hygiene considerations</b>  | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.  |

**9. Physical and chemical properties****Appearance**

|                       |                |
|-----------------------|----------------|
| <b>Physical state</b> | Liquid.        |
| <b>Form</b>           | Liquid.        |
| <b>Color</b>          | Not available. |

**Odor** Not available.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -161.41 °F (-107.45 °C) estimated

**Initial boiling point and boiling range** 210.63 °F (99.24 °C) estimated

**Flash point** 40.1 °F (4.5 °C) estimated

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 1.1 % estimated

**Flammability limit - upper (%)** 4.7 % estimated

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 59.93 hPa estimated

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 784 °F (417.78 °C) estimated

|                                  |                                    |
|----------------------------------|------------------------------------|
| <b>Decomposition temperature</b> | Not available.                     |
| <b>Viscosity</b>                 | Not available.                     |
| <b>Other information</b>         |                                    |
| <b>Density</b>                   | 0.6986 g/cm <sup>3</sup> estimated |
| <b>Explosive properties</b>      | Not explosive.                     |
| <b>Flammability class</b>        | Flammable IB estimated             |
| <b>Oxidizing properties</b>      | Not oxidizing.                     |
| <b>Specific gravity</b>          | 0.7 estimated                      |

## 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.   |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong oxidizing agents.   |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.   |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.                   |
| <b>Skin contact</b> | Causes skin irritation.  |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation.   |
| <b>Ingestion</b>    | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

**Symptoms related to the physical, chemical and toxicological characteristics** Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

| Components               | Species | Test Results          |
|--------------------------|---------|-----------------------|
| Isooctane (CAS 540-84-1) |         |                       |
| <b>Acute</b>             |         |                       |
| <b>Dermal</b>            |         |                       |
| LD50                     | Rabbit  | > 2000 mg/kg          |
| <b>Inhalation</b>        |         |                       |
| LC50                     | Rat     | > 33.52 mg/l, 4 Hours |
| <b>Oral</b>              |         |                       |
| LD50                     | Rat     | > 5000 mg/kg          |

\* Estimates for product may be based on additional component data not shown.

|  |  |
|--|--|
| <b>Skin corrosion/irritation</b>         | Causes skin irritation.  |
| <b>Serious eye damage/eye irritation</b> | Direct contact with eyes may cause temporary irritation.   |
| <b>Respiratory or skin sensitization</b> |  |
| <b>Respiratory sensitization</b>         | Not a respiratory sensitizer.  |
| <b>Skin sensitization</b>                | This product is not expected to cause skin sensitization.  |
| <b>Germ cell mutagenicity</b>            | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>                   | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.                                  |

## IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

## US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

|   |  |
|---|--|
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects. |
| <b>Specific target organ toxicity - single exposure</b>   | May cause drowsiness and dizziness.  |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.  |
| <b>Aspiration hazard</b>                                  | May be fatal if swallowed and enters airways.                                |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful.   |

## 12. Ecological information

|  |   |
|--|---|
| <b>Ecotoxicity</b>                                       | Very toxic to aquatic life with long lasting effects.   |
| <b>Persistence and degradability</b>                     | No data is available on the degradability of this product.  |
| <b>Bioaccumulative potential</b>                         |   |
| <b>Partition coefficient n-octanol / water (log Kow)</b> |   |
| Isooctane  | 5.18  |
| <b>Mobility in soil</b>                                  | No data available.  |
| <b>Other adverse effects</b>                             | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

## 13. Disposal considerations

|  |  |
|--|--|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.   |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.   |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).   |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.   |

## 14. Transport information

### DOT

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1262  |
| <b>UN proper shipping name</b>      | Octanes, solution (Isooctane RQ = 1000 LBS)                             |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 3   |
| <b>Packing group</b>                | II  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | IB2, T4, TP1  |
| <b>Packaging exceptions</b>         | 150   |
| <b>Packaging non bulk</b>           | 202   |
| <b>Packaging bulk</b>               | 242   |

### IATA

|                                   |                              |
|-----------------------------------|------------------------------|
| <b>UN number</b>                  | UN1262                       |
| <b>UN proper shipping name</b>    | Octanes solution (Isooctane) |
| <b>Transport hazard class(es)</b> |                              |
| <b>Class</b>                      | 3                            |

|                                     |   |
|-------------------------------------|---|
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | II  |
| <b>Environmental hazards</b>        | No.   |
| <b>ERG Code</b>                     | 3H  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |   |
| <b>Passenger and cargo aircraft</b> | Allowed.  |
| <b>Cargo aircraft only</b>          | Allowed.  |

**IMDG**

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1262  |
| <b>UN proper shipping name</b>      | OCTANES SOLUTION (Isooctane)  |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 3   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | II  |
| <b>Environmental hazards</b>        |   |
| <b>Marine pollutant</b>             | No.   |
| <b>EmS</b>                          | F-E, S-E  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT**



**IATA; IMDG**



**General information** IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Isooctane (CAS 540-84-1) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - No  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**  
 Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Isooctane (CAS 540-84-1)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations****US - New Jersey RTK - Substances: Listed substance**

Isooctane (CAS 540-84-1)

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Isooctane (CAS 540-84-1)

**US. Massachusetts RTK - Substance List**

Isooctane (CAS 540-84-1)

**US. New Jersey Worker and Community Right-to-Know Act**

Not regulated.

**US. Pennsylvania RTK - Hazardous Substances**

Isooctane (CAS 540-84-1)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Isooctane (CAS 540-84-1)

**US. Rhode Island RTK**

Isooctane (CAS 540-84-1)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada               | Domestic Substances List (DSL)   | No                     |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                | Existing Chemicals List (ECL)  | No                     |
| New Zealand          | New Zealand Inventory  | No                     |
| Philippines          | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |



| Country(s) or region        | Inventory name                                | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | No                     |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

|              |  |
|--------------|--|
| Issue date   | 05-21-2017                                     |
| Version #    | 01   |
| NFPA ratings | Health: 2<br>Flammability: 3<br>Instability: 0 |

**Disclaimer** The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.

Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.